



Modular expandable energy analyzer

UMG 800

Data sheet

Janitza®

Modular expandable energy analyzer
UMG 800



UMG 800
Modular multifunctional meter for
recording energy quantities

Doc. no.: 2.053.225.1.b

Status: 10/2024

The German version is the original version of the documentation.

Subject to technical changes.

The content of our documentation has been compiled with the utmost care and is based on the latest information available to us. Nevertheless, we would like to point out that the updating of this document cannot always be performed simultaneously with the further technical development of our products. Information and specifications can be changed at any time. Please consult www.janitza.com for information on the current version.

Voltage measurement	
Three-phase 4-conductor systems with rated voltages up to	277 V _{LN} / 480 V _{LL} (+/-10%) according to IEC 277 V _{LN} / 480 V _{LL} (+/-10%) according to UL
3-phase 3-conductor systems (grounded) with rated voltages up to	480 V _{L-L} (+/-10%) according to IEC 480 V _{L-L} (+/-10%) according to UL
3-phase 3-conductor systems (non-grounded) with rated voltages up to	480 V _{L-L} (+/-10%) according to IEC 480 V _{L-L} (+/-10%) according to UL
Overvoltage category	300 V CAT III according to IEC 300 V CAT III according to UL
Rated surge voltage	4 kV
Protection of the voltage measurement	1 - 10 A tripping characteristic B (with IEC/UL approval)
Measuring range L-N	0 .. 300 V _{rms} (max. overvoltage 520 V _{rms}) The device only measures if a voltage L-N greater than 20 V _{rms} is applied to L1.
Measuring range L-L	0 .. 520 V _{rms} (max. overvoltage 900 V _{rms}) The device only measures if a voltage L-N of greater than 34 V _{rms} is applied to L1-L2 or L1-L3.
Measuring range N-PE	0 .. 300 V _{rms}
Resolution	0.01 V
Crest factor	2 (referred to measuring range)
Impedance	3 MΩ/phase
Power consumption	approx. 0.1 VA
Sampling frequency	51.2 kHz
Frequency of fundamental oscillation - Resolution	40 Hz .. 70 Hz 0.01 Hz
Harmonics	1 .. 63.

Periphery

RS485 interface	
3-wire connection with A, B, GND.	
Protocol	Modbus RTU/Server (ehemals Slave) Modbus RTU/Gateway
Transmission rate	9.6 kbps, 19.2 kbps, 38.4 kbps, 57.6 kbps, 115.2 kbps
Termination	DIP switches (S1)

Ethernet interfaces	
Connection	2 x RJ45
Function	Modbus Gateway, Embedded Webserver (HTTP)
Protocols	TCP/IP, DHCP-Client (BootP), Modbus/TCP (Port 502), ICMP (Ping), NTP, FTP

USB interface	
Connection	USB 2.0, Type A
Function	Connection for <ul style="list-style-type: none"> · external Display. · USB memory stick (FAT32 formatted) with commissioning configuration.

Connection capacity of the terminals - Supply voltage	
Connectible conductors: Only connect one conductor per terminal point!	
Single core, multi-core, fine-stranded	0.2 - 4 mm ² , AWG 28-12
Wire ferrules (insulated/non-insulated)	0.2 - 2.5 mm ² , AWG 26-14
Tightening torque	0.4 - 0.5 Nm (3.54 - 4.43 lbf in)
Strip length	7 mm (0.2756 in)

Connection capacity of the terminals - Voltage measurement	
Connectible conductors: Only connect one conductor per terminal point!	
Single core	0.5 - 1.5 mm ² , AWG 21-16
Fine-stranded	0.5 - 2.5 mm ² , AWG 21-14
Wire ferrules (insulated/non-insulated)	0.5 - 2.5 mm ² , AWG 21-14
Strip length	10 mm (0.3937 in)

Connection capacity of the terminals - RS485	
Single core, multi-core, fine-stranded	0.2 - 1.5 mm ² , AWG 28-16
Wire ferrules (insulated/non-insulated)	0.2 - 1.5 mm ² , AWG 28-16
Tightening torque	0.2 - 0.25 Nm (1.77 - 2.21 lbf in)
Strip length	7 mm (0.2756 in)

Potential isolation and electrical safety of the interfaces
<p>The interfaces (RS485, Ethernet und USB) have:</p> <ul style="list-style-type: none"> · a double insulation to the voltage measurement inputs. · a functional insulation against each other, to the supply voltage, to the measuring inputs. <p>The interfaces of the connected devices require double or reinforced insulation against mains voltages (according to IEC 61010-1).</p>

optec

Contact us

 Optec AG | Guyer-Zeller-Strasse 14 | CH-8620 Wetzikon ZH

 +41 44 933 07 70  info@optec.ch  www.optec.ch

Janitza electronics GmbH
Vor dem Polstück 6 | 35633 Lahnau |
Germany
Support +49 6441 9642-22
nfo@janitza.com | www.janitza.com

Janitza[®]