



1. ELECTRICAL SPECIFICATIONS

Accuracy is indicated as \pm [% reading + (number dgt * resolution)] at 18°C ÷ 25°C, <75%RH

DC VOLTAGE

Range	Resolution	Accuracy	Input impedance	Overload protection
200.0mV	0.1mV	$\pm(0.7\%rdg+3dgt)$	> 1M Ω	200Vrms
2000mV	1mV			600V DC/AC
20.00V	0.01V			
200.0V	0.1V	$\pm(1.0\%rdg+3dgt)$	> 1M Ω	600V DC/AC
600V	1V			

AC VOLTAGE

Range	Resolution	Accuracy (50 ÷ 60Hz)	Input impedance	Overload protection
200.0V	0.1V	$\pm(1.5\%rdg+12dgt)$	> 1M Ω	600V DC/AC
600V	1V			

DC CURRENT

Range	Resolution	Accuracy	Voltage drop	Overload protection
2000 μ A	1 μ A	$\pm(1.5\%rdg+3dgt)$	200mV	Fast Fuse 200mA / 600V
20.00mA	0.01mA			
200.0mA	0.1mA			
10.00A	0.01A	$\pm(2.5\%rdg+2dgt)$		Fast Fuse 10A / 600V

RESISTANCE AND CONTINUITY TEST

Range	Resolution	Accuracy	Buzzer	Overload protection
200.0 Ω	0.1 Ω	$\pm(1.2\%rdg+4dgt)$	<60 Ω	250Vrms < 15sec
2000 Ω	1 Ω			
20.00k Ω	0.01k Ω			
200.0k Ω	0.1k Ω			
2000k Ω	1k Ω	$\pm(1.5\%rdg+2dgt)$		

DIODE TEST

Function	Test current	Max. open voltage
	approx 1mA	approx 2.8V

BATTERY TEST

Range	Resolution	Accuracy	Test current
1.5V	1mV	$\pm(1.5\%rdg+3dgt)$	100mA
9V	10mV		6mA



2. GENERAL SPECIFICATIONS

Display:

- LCD, 3 ½ dgt, 2000 points plus sign and decimal point
- Automatic polarity indication
- Backlight
- "OL" overrange indication

Features:

- HOLD

Low battery indication:

- "BAT" appears when the battery voltage is low

Operating temperature:

- 0 °C to 50 °C, <70%RH

Storage temperature:

- -20 °C to 60 °C, <80%RH

General information:

- Max altitude: 2000m
- Pollution degree: 2
- Insulation: double insulation

Power supply:

- 1x9V battery NEDA 1604 IEC 6F22
- Battery life: ca 30h (backlight ON), ca 130h (backlight OFF)
- Protection fuses: fast 10A/600V, 5x20mm (**10A** input),
fast 200mA/600V, 5x20mm (**mA μ A** input)

Dimensions (L x W x H):

- 150 x 70 x 48mm
- Mechanical protection: IP40

Weight (included battery):

- 255g

Applied standards:

- Safety : IEC/EN61010-1 CAT III 600V to ground
- EMC: IEC/EN61326-1

This instrument satisfies the requirements of Low Voltage Directive 2014/35/EU (LVD) and of EMC Directive 2014/30/EU

This instrument satisfies the requirements of 2011/65/EU (RoHS) directive and 2012/19/EU (WEEE) directive

optec
energie ist messbar

Optec AG | Guyer-Zoller-Strasse 14 | CH-9620 Wetzikon ZH
Telefon: +41 44 933 07 70 | Telefax: +41 44 933 07 77
E-Mail: info@optec.ch | Internet: www.optec.ch